

# PATHFINDER RECESSED LEAD ACID EMERGENCY

Small but powerful, this halogen emergency luminaire recesses discretely into most ceilings for superb illuminance in the event of a power failure. This economy version with a lead acid battery is only suitable for accessible ceilings or inaccessible ceilings with a good cavity above. CATS II monitored version available.



CATALOGUE NUMBER:      STANDARD:      **PF10L**  
CATS II:                      **PFC10L**

## SPECIFICATIONS:

SUPPLY:	240V+5% 50Hz .03A. 7VA
LAMP:	6V 10W Tungsten Halogen G4
BATTERY:	Lead acid sealed 6V 6.5AH
CHARGER:	Taper charge
CASE:	White enamelled zincseal steel
REFLECTOR:	White painted zinc sealsteel <b>PF10L/ PFC10L</b> (125mm Diam.) <b>PFM10L</b> (75mm Diam.)
CUT-OUT SIZE:	<b>PF10L/PFC10L</b> (100mm)
STANDARD:	Charge indicator LED and test switch
OPTIONAL EXTRA:	1.5M Flex and Plug / Protective cover on reflector
GARANTEE:	Against faulty parts or workshop - 12 months
SERVICE:	White Lite operates a service section to fully service any White Lite fitting
COMPLIANCE:	AS/NZ 2293.1 1995, Building Code of Australia 1990, S.I.S.I.R. CP19
CERTIFICATION:	Co D25 C90 D25    See Information Sheet for spacings table.

## MAXIMUM SPACINGS

MOUNTING HEIGHT:	2.1	2.7	3.0	3.6	4	4.5	5	6	7	8	9	10	15
D25	14.2	15.3	15.7	16.5	16.9	17.3	17.7	18.1	18.3	18.2	17.9	17.3	7.7



Head Office:

42 Beaumont Road Mt Kuring-gai NSW 2080 Australia PO Box 47 Mt Kuring-gai NSW 2080 Australia  
PHONE: +61 2 9457 8877 FAX: +61 2 9457 9596

CATS II MONITORING AVAILABLE

