

PATHFINDER-RECESSED NICAD EMERGENCY

Small but powerful, this halogen emergency luminaire recesses discretely into most ceilings for superb illumination in the event of a power failure.
CATS II monitored version available.



CATALOGUE NUMBER:	STANDARD:	Single	Dual Rate	Miniature	Polycarbonate Outer
	CATS II:	PF10 PFC10	PFD10 PFDC10	PFM10 PFMC10	PFPI0 PFPC10

SPECIFICATIONS:

SUPPLY:	240V±5% 50Hz .03A 7VA	
LAMP:	6V 10W Tungsten Halogen G4	
BATTERY:	Nickel Cadmium high temperature to 70°C	
CHARGER:	Single rate: PF10/PFM10 Two rate - high C/10 low C/20: PFD10/PFMD10	
CASE:	White enamelled zinc seal steel	
REFLECTOR:	White painted zinc seal alloy PF10/PFD10 (125mm) PFM10/PFMD10 (75mm) Miniature	
CUT OUT SIZE:	PF10/PFD10 (100mm) PFM10/PFMD10 (60mm)	
OPTIONAL EXTRA:	1.5m Flex plug / protective cover on reflector	
STANDARD:	Charge indicator LED and test switch	
GUARANTEE:	Against faulty parts or workmanship - 12 months	
SERVICE:	White Lite operates a service section to fully service any White Lite fitting	
COMPLIANCE:	AS/NZ 2293.1 1995, Building Code of Australia 1990, S.I.S.I.R. CP19	
CERTIFICATION:	Co D20 C90 D20 See Information Sheet for spacings table.	

MAXIMUM SPACINGS

MOUNTING HEIGHT:	2.1	2.7	3.0	3.6	4	4.5	5	6	7	8	9	10
D20	13.2	14.1	14.5	15.1	15.5	15.8	16.1	16.4	16.3	16.0	15.4	14.5



Head Office:

42 Beaumont Road Mt Kuring-gai NSW 2080 Australia PO Box 47 Mt Kuring-gai NSW 2080 Australia
PHONE: +61 2 9457 8877 FAX: +61 2 9457 9596

CATS II MONITORING AVAILABLE

